

DEHUMIDIFIER

Professional-dehumidifiers with electric control



DEHUMIDIFIER

AMT Series Drying and dehumidifying more reliable than sun and wind

REMKO AMT

No moisturised walls, musty smells, and mould - dry quickly and efficiently at the press of a button

Windows and doors can also only be insulated to a certain degree; moisture penetrates even through thick cement walls. Dangerous moisture that leads more quickly to mould and rust than expected and damage deposited materials, electrical installations, perishables, files, and much more. During the manufacturing of cement, mortar, plaster, and so on, large volumes of water are required for the hardening process. Even processed construction elements like bricks, gas cement, and so on may contain water to an extent that should not be underestimated.

The AMT can even be used to dry laundry

REMKO dehumidifiers are perfectly suited for rooms in cellars, hobby rooms, conservatories, bathrooms, workrooms, recreation rooms, archives, warehouses, and so on.



REMKO Room hygrostat, **Type HR-1**, for fully automatic control, ready for plug assembly

This can be avoided.

- wet walls
- musty smells
- rust
- condenswater water
- formation of mould

To prevent damage due to moisture and cost intensive work interruptions, the use of a dehumidifier is recommended.

The REMKO AMT mobile dehumidifier is easy to operate and guarantees constant, malfunction-free use around the clock.



REMKO Dehumidifier are stackable

The REMKO dehumidifiers functions as follows:

A fan built into the unit conducts the moist room air through an evaporator and cools it below the dew point. In this way, the excess water vapour is exuded as condensate and can be conducted to a water tank. The dehumidified air is blown out again when moisture is removed.

- Easy service thanks to a clearly arranged construction
- Compressor protection through start-up delay
- Efficient through modern compressor technology
- Very low operating costs
- Very good handling with large wheels and ergonomically shaped handles
- Portable with very low intrinsic weight
- Interference-free, constant use, even around the clock
- Fully automatic controls
- Compact and thus easily transported in a car
- Stackable




REMKO AMT 40-E



Technical data

Series		AMT 40-E	AMT 55-E	AMT 80-E	AMT 110-E
Max. daily dehumidification capacity	Liter/Tag	38	55	80	107
at 30°C and 80% relative humidity	Liter/Tag	32,4	48,0	69,6	93,1
Application temperature range	°C	3-32	3-32	3-32	3-32
Application humidity range	% r.F.	40-100	40-100	40-100	40-100
Air volume	m³/h	290	430	800	1200
Condensate tank capacity	Liter	8	18	18	_
Electronic starting fuse		standard	standard	standard	standard
Operating hour counter		standard	standard	standard	standard
Hot gas defrosting unit		standard	standard	standard	standard
Dust filter		standard	standard	standard	standard
Power supply	V/Hz	230/1~/50			
Max. power consumption	kW	0,75	0,90	1,10	1,70
Depth	mm	490	530	535	605
Width	mm	480	605	605	710
Height	mm	640	705	790	895
Height incl. handle	mm	935	935	935	935
Weight	kg	35	43	47	63
Ref. No.		612400	612550	612800	612900
Other accessories					
Hygrostat, Type HR-1, ready for plug assembly		1011200	1011200	1011200	1011200
adjustment 20-80% relative humidity					
Condenswater pump, built-in,		1011205	1011205	1011205	-
incl. 10 m condensate pipe, Ø 6 mm					
Condenswater pipe, separate, Ø 6 mm , lfdm.		1011206	1011206	1011206	-





Easy service due to a easy access panels





REMKO INTERNATIONAL

... and somewhere near you! Take advantage of our experience and consulting services.



Consulting

Through intensive training, we make sure the expert knowledge of our consultants is always up-to-date. This has given us the reputation of being more than just a good, reliable supplier: REMKO, a partner that helps solve problems.

Sales

REMKO not only provides an extensive sales network in Germany and abroad, but also unusually highly qualified sales experts. REMKO sales representatives are more than just salespeople: they must also be customer consultants in air conditioning and heating technology.

Customer care

Our devices function precisely and reliably. If a malfunction appears, however, REMKO Customer Care is on the job. Our extensive network of experienced dealers guarantees you constant, short-term, and reliable service.

REMKO GmbH & Co. KG Air Conditioning and Heating Technology

Im Seelenkamp 12 · D-32791 Lage PO Box 1827 · D-32777 Lage Phone: +49 5232 606-0

Fax: +49 5232 606-260 E-mail: info@remko.de Internet: www.remko.de

Hotline

Germany

+49 5232 606-0

International

+49 5232 606-130



